


HALA CLIPS
THERMAL MANAGEMENT

CREATING CLOSEST CONTACT



HALA CLIPS THERMAL MANAGEMENT

CREATING CLOSEST CONTACT




BENEFITS

- Maximized thermal contact (even at minimum package height)
- FE-simulation optimised stress behaviour
- Optimized interaction with HALA Thermal Interface Materials
- Mounting friendly design
- Easy chip identification by apertures

We design your tailor-made clip solution.

Please contact us as your development partner.



Release 04 / 2020

HALA CLIP TO 220-1

Dimensions


- Force range: ca. 55...85 N
- Pressure range: ca. 35...55 N/cm² (50...80 PSI) for different types of TO 220 packages (Surface area TO 220 approx. 1.6 cm²)

HALA CLIP TO 247-1


Dimensions

- Force range: ca. 95...110 N
- Pressure range: ca. 28...32 N/cm² (40...47 PSI) for different types of TO 247 packages (Surface area TO 247 approx. 3.4 cm²)

FORCE VS. DEFLECTION



FORCE VS. DEFLECTION



All technical data and information are without warranty and believed to be reliable and accurate corresponding to the latest state of the art. Since the products are not provided to conform with mutually agreed specifications and their use and processing are unknown we cannot guarantee results, freedom from patent infringement, or their suitability for any application. Product testing by the applicant is recommended. We reserve the right of changes.